

"Autofill"

Pumpless Pressurisation Unit



Complies with the Water Regulations for filling of "non-house" heating or chilled water systems

- **Extremely Compact** – only 300 mm square
- **No filling loop required** – features internal quick fill valve
- **No power required for quick fill**
- **No integral tank** – sealed system reduces risk of airborne legionella
- **No pump** (model AFS)
- **Volt-free high and low cut-out switches** – adjustable
- **Serviceable** – all components accessible
- **Sizes** – 15 and 22 mm

"Autofill" utilises the supply pressure to reliably fill and pressurise sealed heating or chilled water systems, whilst providing fluid category 4 protection.

The "Autofill" is supplied fully assembled with inlet and outlet stainless steel braided hoses, servicing valves and push-fit connections.

Installation can be further facilitated using the wall mounting bracket (pictured).

Two models of "Autofill" are available, AFS and AFP. Model AFP features a built-in booster pump for applications where boosted cold water is unavailable. The booster pump can be retro-fitted on site.



Wall mounting bracket (Model AFBRA)

The 22 mm "Autofill" fills faster than the 15 mm and is suitable for systems greater than 200 kW.

Applications

Primary heating systems • Under floor heating • Refrigerating equipment • Chilled water circuits • Industrial processes

UK WATER REGULATIONS KIWA approved

The Water Regulations Solution Specialist

FOR FURTHER INFORMATION ON "AUTOFILL" AND MANY OTHER PRODUCTS PLEASE VISIT OUR WEBSITE AT:
www.arrowvalves.co.uk



ARROW VALVES LTD

☎ 01442 823123 ☎ 01442 823234

✉ info@arrowvalves.co.uk www.arrowvalves.co.uk